SAFETY DATA SHEET

#### RUPERT, GIBBON & SPIDER PO BOX 425, HEALDSBURG CA, 95448 TEL: (707) 433-9577 FAX: (707) 433-4906



Contact Information: Rupert Gibbon & Spider 1147 Healdsburg Ave. Healdsburg, CA 95448 800-442-0455

CHEMTREC (24HR Emergency Telephone), call: I-800-424-9300 International CHEMTREC, call: I-703-527-3887 For non-emergency assistance, call: 800-442-0455

Dye-Na-Flow SDS No: 801-830 Date: 11/24/2015

### I. Chemical, Product and Company Identification

PRODUCT NAME:	Dye-Na-Flow
CATALOG CODES:	All Colors
CAS#:	NA
CI#:	NA

## Toxicological Data on Ingredients: 2. Hazards Identification

This material is not hazardous under the criteria of Federal OSHA hazard communication standard 29 CFR 1910 1200.

OTHER HAZARDS: No data available

#### 3. Composition and Information on Ingredients

Composition:	CAS #	% by Weight
Diethylaminoethanol	<.1%	cas # 100-37-8
Acrylic polymer(s)	= 15 %</td <td></td>	
Residual monomers	= .01%</td <td></td>	
Propylene glycol	<1%	
Titanium Dioxide	>/= .5% (830 WHITE ONLY)	

## 4. First Aid Measures

EYE CONTACT:

wear contact lenses while handling.

Wash immediately with large amounts of water for 15 minutes. Get medical attention if necessary. Do not

INGESTION: Dilute with water and get medical attention immediately. Do not induce vomiting.

INHALATION:

Aside from the information found under description of first aid measures and indication of immediate medical attention and special treatment needed any additional important information and effects are described in Section 11.

Move to fresh air.

#### Section 5: Fire and Explosion Data

FLAMMABILITY OF THE PRODUCT:	Not Flammable
AUTO-IGNITION TEMPERATURE:	Unknown
FLASH POINTS:	Not combustable

### SAFETY DATA SHEET

RUPERT, GIBBON & SPIDER PO BOX 425, HEALDSBURG CA, 95448 TEL: (707) 433-9577 FAX: (707) 433-4906

Flammable Limits:	
PRODUCTS OF COMBUSTION:	NA
FIRE HAZARDS IN PRESENCE	
OF VARIOUS SUBSTANCES:	NA
SPECIAL HAZARDS:	(arising from the substance or mixture hazardous combustion products:) No data available
UNUSUAL FIRE/EXPLOSION HAZARDS:	Material in liquid form can splatter above 100 degrees Celsius or 212 degrees Fahrenheit. dried product can burn.
SUITABLE EXTINGUISHING MEDIA:	Use extinguishing media appropriate for surrounding fire.
UNSUITABLE EXTINGUISHING MEDIA:	No data available.
ADVICE FOR FIREFIGHTERS	
FIREFIGHTING PROCEDURES:	No data available
SPECIAL PROTECTIVE EQUIPMENT	
FOR FIREFIGHTERS:	Wear a self contained breathing apparatus and protective suit.
Section 6: Accidental Release Measures	
PERSONAL PRECAUTIONS,	
AND EMERGENCY PROCEDURES:	Use personal protective equipment. keep people away from the spill or leak. Material may cause slippery conditions.
ENVIRONMENTAL PRECAUTIONS:	Caution keep spills and cleaning runoff out of municipal sewers and open bodies of water.
METHODS AND MATERIALS FOR	
CONTAINMENT AND CLEANING	
UP SPILLED PRODUCT:	Contain the spill immediately with inert material such as kitty litter, sand or earth. Transfer the spilled paint and solid material to separate suitable containers for recovery or responsible disposal.
Section 7: Handling and Storage	
PRECAUTIONS FOR SAFE HANDLING:	Avoid contact with eyes skin and clothing.Wash their release after handling. Keep jars and containers tightly closed when not in use.
CONDITIONS FOR SAFE STORAGE:	Do not freeze. product stability will be affected. Stir or shake well before use.
STORAGE STABILITY/STORAGE TEMPERATURE:	
I - 49 degrees Celsius 434 to 120 degrees Fahrenheit	. Do not freeze. Formaldehyde may be generated under acidic

I - 49 degrees Celsius 434 to 120 degrees Fahrenheit. Do not freeze. Formaldehyde may be generated under acidic conditions. maintain adequate ventilation under these conditions to prevent exposure to formaldehyde above the recommended ceiling of .3 ppm. acidic conditions will also affect stability of product. avoid acidic conditions for material.

#### **SDS**

SDS

SAFETY DATA SHEET

RUPERT, GIBBON & SPIDER PO BOX 425, HEALDSBURG CA, 95448 TEL: (707) 433-9577 FAX: (707) 433-4906

# Section 8: Exposure Controls/Personal Protection

INDIVIDUAL PROTECTION MESSURES' EYE AND FACE PROTECTION: Safety glasses with side shields. SKIN AND HAND PROTECTION: Gloves Section 9: Physical and Chemical Properties PHYSICAL STATE AND APPEARANCE: Colored liquid. Low-medium viscosity liquid ODOR: slight acrylic odor TASTE: NA MOLECULAR WEIGHT: NA COLOR: see label color of product pH (1% SOLN/WATER): 9.5 SPECIFIC GRAVITY: 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 FREEZING POINT: 0C / 32 F BOILING POINT: 10 C / 32 F BOILING POINT: No data available FLASH POINT: No data available FLASH POINT: No data available FLASH POINT: No data available FLASH POINT: NA LOWER EXPLOSION LIMIT: NA LOWER EXPLOSION LIMIT: NA UPPER EXPLOSION LIMIT: NA CRITICAL TEMPERATURE: NA VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: NA VAPOR TRESSURE: NA NA VAPOR TRESSURE: NA NA VAPOR TRESSURE: NA NA VAPOR TRESSURE: NA N	PROTECTIVE MEASURES:	Facilities storing or utilizing this material and large volume should be equipped with an eyewash station.
SKIN AND HAND PROTECTION: Gloves   Section 9: Physical and Chemical Properties Colored liquid. Low-medium viscosity liquid   PHYSICAL STATE AND APPEARANCE: Colored liquid. Low-medium viscosity liquid   ODOR: slight acrylic odor   TASTE: NA   MOLECULAR WEIGHT: NA   COLOR: see label color of product   pH (1% SOLN/WATER): 9.5   SPECIFIC GRAWITY: 1.2   RELATIVE DENSITY (WATER=1): +/ 1.2   RELATIVE DENSITY (WATER=1): +/ 1.2   RELETING POINTS: 100 C/ 212F   BOLLING POINTS: 100 C/ 212F   BOLLING POINTS: Non-combustible   EVAPORATION RATE(BUTYL ECETATE = 1): <1	INDIVIDUAL PROTECTION MEASURES/	
Section 9: Physical and Chemical Properties PHYSICAL STATE AND APPEARANCE: Colored liquid. Low-medium viscosity liquid ODOR: slight acrylic odor TASTE: NA MOLECULAR WEIGHT: NA COLOR: see label color of product pH (1% SOLN/WATER): 9.5 SPECIFIC GRAVITY: 1.2 RELATIVE DENSITY (WATER-1): +/ 1.2 RELATIVE DENSITY (WATER-1): +/ 1.2 RELATIVE DENSITY (WATER-1): 0 C / 32 F BOILING POINTS: 100 C / 212F MELTING POINTS: Non-combustible FLASH POINT: Non-combustible EVAPORATION RATE (BUTYL ECETATE = 1): < 1 FLAMMABILITY (SOLID, GAS): NA LOWER EXPLOSION LIMIT: NA LOWER EXPLOSION LIMIT: NA UPPER EXPLOSION LIMIT: NA CRITICAL TEMPERATURE: NA VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: 23.665 @ 20C water VAPOR PRESSURE: 30% ODOR THRESHOLD: NA VOLATILITY: < 30% ODOR THRESHOLD: NA WATER/OIL DIST. COEFF: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: DIJurtible AUTO IGNITION TEMPE AUTO IGNITION TEMPE AUTO IGNITION TEMPE NA DECOMPOSITION TEMPE NA DECOMPOSITION TEMPE NA DECOMPOSITION TEMPE NA DECOMPOSITION TEMPE NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	EYE AND FACE PROTECTION:	Safety glasses with side shields.
PHYSICAL STATE AND APPEARANCE: Colored liquid. Low-medium viscosity liquid ODOR: slight acrylic odor TASTE: NA MOLECULAR WEIGHT: NA COLOR: see label color of product pH (1% SOLN/WATER): 9.5 SPECIFIC GRAVITY: 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): 0 C/ 32 F BOILING POINT: 0 C/ 32 F BOILING POINT: No data available FLASH POINT: No data available EVAPORATION RATE(BUTYL ECETATE = 1): <1 FLASH POINT: NA LOWER EXPLOSION LIMIT: NA LOWER EXPLOSION LIMIT: NA LOWER EXPLOSION LIMIT: NA CRITICAL TEMPERATURE: NA VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: NA VAPOR DENSITY: NA VAPOR DENSITY: NA VOLATILITY: < 30% ODOR THRESHOLD: NA WATER/OIL DIST. COEFF: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: NA	SKIN AND HAND PROTECTION:	Gloves
PHYSICAL STATE AND APPEARANCE: Colored liquid. Low-medium viscosity liquid ODOR: slight acrylic odor TASTE: NA MOLECULAR WEIGHT: NA COLOR: see label color of product pH (1% SOLN/WATER): 9.5 SPECIFIC GRAVITY: 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): +/- 1.2 RELATIVE DENSITY (WATER=1): 0 C/ 32 F BOILING POINT: 0 C/ 32 F BOILING POINT: No data available FLASH POINT: No data available EVAPORATION RATE(BUTYL ECETATE = 1): <1 FLASH POINT: NA LOWER EXPLOSION LIMIT: NA LOWER EXPLOSION LIMIT: NA LOWER EXPLOSION LIMIT: NA CRITICAL TEMPERATURE: NA VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: NA VAPOR DENSITY: NA VAPOR DENSITY: NA VOLATILITY: < 30% ODOR THRESHOLD: NA WATER/OIL DIST. COEFF: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: NA	Section 9: Physical and Chemical Properties	
TASTE:NAMOLECULAR WEIGHT:NACOLOR:see label color of productpH (1% SOLN/WATER):9.5SPECIFIC GRAVITY:1.2RELATIVE DENSITY (WATER=1):+/- 1.2RELATIVE DENSITY (WATER=1):/- 1.2BOILING POINTS:100 C/ 32 FBOILING POINTS:100 C/ 212FMELTING POINT:Non-combustibleFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1		Colored liquid. Low-medium viscosity liquid
MOLECULAR WEIGHT:NACOLOR:see label color of productPH (1% SOLN/WATER):9.5SPECIFIC GRAVITY:1.2RELATIVE DENSITY (WATER=1):+/- 1.2RELATIVE DENSITY (WATER=1):+/- 1.2BOILING POINTS:0 C/ 32 FBOILING POINTS:100 C/ 212FMELTING POINT:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE =1):<1	ODOR:	slight acrylic odor
COLOR:see label color of productpH (1% SOLN/WATER):9.5SPECIFIC GRAVITY:1.2RELATIVE DENSITY (WATER=1):+/-1.2FREEZING POINT:0 C/ 32 FBOILING POINTS:100 C/ 212FBOILING POINT:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	TASTE:	NA
pH (1% SOLN/WATER):9.5SPECIFIC GRAVITY:1.2RELATIVE DENSITY (WATER=1):+/- 1.2FREEZING POINT:0 C/ 32 FBOILING POINTS:100 C/ 212FMELTING POINT:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	MOLECULAR WEIGHT:	NA
SPECIFIC GRAVITY:1.2RELATIVE DENSITY (WATER=I):+/- 1.2FREEZING POINT:0 C/ 32 FBOILING POINTS:100 C/ 212FMELTING POINT:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	COLOR:	see label color of product
RELATIVE DENSITY (WATER=1):+/- 1.2FREEZING POINT:0 C/ 32 FBOILING POINT:100 C/ 212FMELTING POINT:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	pH (1% SOLN/WATER):	9.5
FREEZING POINT:0 C/ 32 FBOILING POINTS:100 C/ 212FMELTING POINT:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	SPECIFIC GRAVITY:	1.2
BOILING POINTS:I00 C/ 212FMELTING POINTS:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	RELATIVE DENSITY (WATER=I):	+/- 1.2
MELTING POINT:No data availableFLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	FREEZING POINT:	0 C/ 32 F
FLASH POINT:Non-combustibleEVAPORATION RATE(BUTYL ECETATE = 1):<1	BOILING POINTS:	100 C/ 212F
EVAPORATION RATE(BUTYL ECETATE = I): <i< td="">FLAMMABILITY (SOLID, GAS):NALOWER EXPLOSION LIMIT:NAUPPER EXPLOSION LIMIT:NACRITICAL TEMPERATURE:NAVAPOR PRESSURE:22.665 @ 20C waterVAPOR PRESSURE:NAVAPOR DENSITY:NAVOLATILITY:&lt; 30%</i<>	MELTING POINT:	No data available
FLAMMABILITY (SOLID, GAS):NALOWER EXPLOSION LIMIT:NAUPPER EXPLOSION LIMIT:NACRITICAL TEMPERATURE:NAVAPOR PRESSURE:22.665 @ 20C waterVAPOR PRESSURE:NAVAPOR DENSITY:NAVOLATILITY:< 30%	FLASH POINT:	Non-combustible
LOWER EXPLOSION LIMIT: NA UPPER EXPLOSION LIMIT: NA CRITICAL TEMPERATURE: NA VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: NA VAPOR DENSITY: NA VOLATILITY: <30% ODOR THRESHOLD: NA WATER/OIL DIST. COEFF: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	EVAPORATION RATE(BUTYL ECETATE = 1):	<
UPPER EXPLOSION LIMIT:NACRITICAL TEMPERATURE:NAVAPOR PRESSURE:22.665 @ 20C waterVAPOR PRESSURE:NAVAPOR DENSITY:NAVAPOR DENSITY:NAVOLATILITY:< 30%	FLAMMABILITY (SOLID, GAS):	NA
CRITICAL TEMPERATURE:NAVAPOR PRESSURE:22.665 @ 20C waterVAPOR PRESSURE:NAVAPOR DENSITY:NAVOLATILITY:< 30%	LOWER EXPLOSION LIMIT:	NA
VAPOR PRESSURE: 22.665 @ 20C water VAPOR PRESSURE: NA VAPOR DENSITY: NA VOLATILITY: <30% ODOR THRESHOLD: NA WATER/OIL DIST. COEFF: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA KINETIC VISCOSITY: NA	UPPER EXPLOSION LIMIT:	NA
VAPOR PRESSURE: NA VAPOR DENSITY: NA VOLATILITY: <30% ODOR THRESHOLD: NA WATER/OIL DIST. COEFF: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA KINETIC VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	CRITICAL TEMPERATURE:	NA
VAPOR DENSITY:NAVOLATILITY:< 30%	VAPOR PRESSURE:	22.665 @ 20C water
VOLATILITY:< 30%	VAPOR PRESSURE:	NA
ODOR THRESHOLD: NA WATER/OIL DIST. COEFF.: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	VAPOR DENSITY:	NA
WATER/OIL DIST. COEFF.: NA IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	VOLATILITY:	< 30%
IONICITY (IN WATER): Anionic DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	ODOR THRESHOLD:	NA
DISPERSION PROPERTIES: Suspention SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	WATER/OIL DIST. COEFF.:	NA
SOLUBILITY IN WATER: Dilutible AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	IONICITY (IN WATER):	Anionic
AUTO IGNITION TEMP: NA DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	DISPERSION PROPERTIES:	Suspention
DECOMPOSITION TEMP: NA VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	SOLUBILITY IN WATER:	Dilutible
VISCOSITY: 4000-46000cps KINETIC VISCOSITY: NA	AUTO IGNITION TEMP:	NA
KINETIC VISCOSITY: NA	DECOMPOSITION TEMP:	NA
	VISCOSITY:	4000-46000срѕ
EXPLOSIVE PROPERTIES: NA	KINETIC VISCOSITY:	NA
	EXPLOSIVE PROPERTIES:	NA

# ET 06

SDS			SAFE	ETY DATA SHEE
RUPERT, GIBBON & SPIDER	PO BOX 425, HEALDSB	URG CA, 95448	TEL:(707) 433-9577	FAX: (707) 433-490
OX	(IDIZING PROPERTIES:	NA		
	MELECULAR WEIGHT:	NA		
Section 10: Stability and	Reactivity Data			
	<b>REACTIVITY</b> :	No data availabl	e	
	CHEMICAL STABILITY:	Stable		
POSSIBILITY OF HAZA	ARDOUS REACTIONS:	None known		
		Product may une	dergo polymerization	
СО	NDITIONS TO AVOID:	extreme cold or	heat	
INCO	MPATIBLE MATERIALS:	Strong acids		
HAZARDOUS DECOMP	OSITION PRODUCTS:	Thermal decom	position may yield acry	lic monomers
Section 11:Toxicological	Information			
	ROSION/IRRITATION:	Skin irritation m	ay occur	
SERIOUS EYE	DAMAGE/IRRITATION:	No eye irritatio	n	
	sensitization:	No data availabl	e	
SPECIFIC TARGET ORGAI	N SYSTEMIC TOXICITY:	No data availabl	e	
	CARCINOGENICITY:	No data availabl	e	
REPR	ODUCTIVE TOXICITY:	No data availabl	e	

No data available

No data available

at this time.

**Residual Monomers** 

No information at this time.

# Section 12: Ecological Information

COMPONENTS INFLUENCING TOXICOLOGY:

No infe	GENERAL INFORMATION:
Acute	ACRYLIC POLYMERS:
Acute	<b>RESIDUAL MONOMERS:</b>
NA	PERSISTENCE AND DEGRADABILITY:
Biodeg	ACRYLIC POLYMERS:
NA	<b>RESIDUAL MONOMERS:</b>
No rel	BIODEGRADABILTY:
NA	BIOACUMULATION POTENTIAL:
NA	ACRYLIC POLYMERS:
No rel	BIOACUMULATION:
NA	<b>RESIDUAL MONOMERS:</b>
No rel	BIOACUMULATION:
No rel	MOBILITY IN SOIL:

MUTAGENICITY:

ASPIRATION HAZARD:

**ACRYLIC POLYMERS:** 

**RESIDUAL MONOMERS:** 

ACUTE INHALATION TOXICITY:

formation available at this time toxicity to fish: no relevant data found toxicity to fish: no relevant data found gradabilty: no relevant data found elevant data found elevant data found elevant data found elevant data available

Acute inhalation toxicity: The LC 50 has not been determined

The LC 50 has not been determined at this time.

#### RUPERT, GIBBON & SPIDER PO BOX 425, HEALDSBURG CA, 95448 TEL: (707) 433-9577 FAX: (707) 433-4906

WASTE DISPOSAL: Dispose in accordance with local regulation.

#### Section 14: Transport Information

Not Regulated/Not dangerous according to the above specifications.

#### Section 15: Other Regulatory Information

#### **OSHA Hazard Communication Standard**

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.1200).

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product does not contain any chemicals which are listed in Section 313 at or above de minimis concentrations.

#### Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

#### Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

#### United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### California Prop 65

This product does NOT contain any chemicals known to the state of California to cause cancer.

#### Section 16: Other Information

The information contained in this SDS is based on data from sources considered to be reliable but Rupert, Gibbon & Spider Inc. does not guarantee the accuracy or completeness thereof. Rupert, Gibbon & Spider Inc. urges each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology or fire and understand the data in this SDS.