Safety Data Sheet



Revision Number: 001.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type:

Restriction of Use:

Company address:

Henkel Corporation

One Henkel Way

Loctite Power Grab Heavy Duty Express Acrylic Adhesive None identified IDH number:

2032666

Region:United StatesContact information:Telephone: +1 (800) 624-7767MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCYPhone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

WARNING:

Rocky Hill, Connecticut 06067

EMERGENCY OVERVIEW ABRASION COULD RELEASE RESPIRABLE PARTICLES OF SILICA QUARTZ, A CANCER HAZARD BY INHALATION. NORMAL USE OF THIS PRODUCT CAUSES NO SUCH RELEASE.

CAUSES SERIOUS EYE IRRITATION.

| | HAZARD CLASS | HAZARD CATEGORY |
|----------------|--------------|-----------------|
| EYE IRRITATION | | 2A |
| | | |
| | PICTOGRAM(S) | |



Precautionary Statements

| Prevention: Response: | Wash thoroughly after handling. Wear eye and face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
|--------------------------|---|
| Storage: | Not prescribed |
| Disposal: | Not prescribed |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

| Hazardous Component(s) | CAS Number | Percentage* |
|---|------------|-------------|
| Limestone | 1317-65-3 | 30 - 60 |
| Silicon dioxide | 7631-86-9 | 1 - 5 |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | 0.1 - 1 |
| Quartz (SiO2) | 14808-60-7 | 0.1 - 1 |

3. COMPOSITION / INFORMATION ON INGREDIENTS

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

| 4. FIRST AID MEASURES | | |
|--|--|--|
| Inhalation: | Move to fresh air. If symptoms persist, seek medical advice. | |
| Skin contact: | Wash with soap and water. If symptoms develop and persist, get medical attention. | |
| Eye contact: | Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention. | |
| Ingestion: | Do not induce vomiting. Seek medical advice. | |
| Symptoms: | See Section 11. | |
| 5. FI | RE FIGHTING MEASURES | |
| Extinguishing media: | carbon dioxide, foam, powder, water spray jet, fine water spray | |
| Special firefighting procedures: Not available. | | |
| Unusual fire or explosion hazards: None known. | | |
| Hazardous combustion products: | Oxides of carbon. | |
| 6. ACCID | DENTAL RELEASE MEASURES | |
| Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel. | | |
| Environmental precautions: | Environmental precautions: None known | |
| Clean-up methods: Scrape up as much material as possible. Clean residue with soap and wat | | |
| 7. HANDLING AND STORAGE | | |

Handling:

Storage:

Protect from freezing. Store in a cool, dry area.

Avoid contact with eyes. Avoid prolonged or repeated skin contact with this material. Do not taste or swallow. Keep out of the reach of children.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER | |
|---|---|---|------------------------|-------------------------------------|--|
| Limestone | 10 mg/m3 TWA Total dust. | 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None | |
| Silicon dioxide | 6 mg/m3 TWA | 20 MPPCF TWA 0.8 mg/m3 TWA | None | 3 mg/m3 TWA Respirable fraction. | |
| Distillates (petroleum), hydrotreated light | None | None | None | None | |
| Quartz (SiO2) | 0.025 mg/m3 TWA Respirable fraction. | 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust. | None | None | |
| Engineering controls: | Not nor | mally needed. | | | |
| Respiratory protection: | No pers | sonal respiratory protectiv | ve equipment normally | required. | |
| Eye/face protection: | No spec | cial measures required if | used properly. | | |
| Skin protection: | Skin protection: No special measures required if used properly. | | | | |
| 9. PH | IYSICAL AND C | HEMICAL PROPI | ERTIES | | |
| | 0.111 | | | | |
| Physical state: | Solid | | | | |
| Color: | White | | | | |
| Odor: | Acrylic | , | | | |
| Odor threshold: | | Not available. | | | |
| pH: | 8.5 | | | | |
| Vapor pressure: | | Not available. | | | |
| Boiling point/range: | | > 100 °C (> 212°F) | | | |
| Melting point/ range: | | Not available. | | | |
| Specific gravity: | 1.345 (\ | 1.345 (Water = 1) | | | |
| Vapor density: | | | | | |
| | 0.62 (A | ir = 1) | | | |
| Flash point: | > 100 ° | ir = 1) C (> 212°F) ; Not classifi | | | |
| Flash point: | > 100 ° Classifi | ir = 1) C (> 212°F) ; Not classifi cation Guidelines Part 17 | | | |
| Flash point: Flammable/Explosive limits - lower: | > 100 ° Classifi Not ava | ir = 1) C (> 212°F) ; Not classifi cation Guidelines Part 17 ilable. | | | |
| Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: | > 100 [°] Classifi Not ava Not ava | ir = 1) C (> 212°F) ; Not classifi cation Guidelines Part 17 ilable. ilable. | | | |
| Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: | > 100 ^{°o} Classifi Not ava Not ava Not ava | ir = 1) C (> 212°F) ; Not classific cation Guidelines Part 17 ilable. ilable. ilable. | | | |
| Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: | > 100 ^{°o} Classifi Not ava Not ava Not ava 1 (Wate | ir = 1) C (> 212°F) ; Not classific cation Guidelines Part 17 ilable. ilable. ilable. er = 1) | | | |
| Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: | > 100 °/ Classifi Not ava Not ava Not ava 1 (Wate emulsifi | ir = 1) C (> 212°F) ; Not classific cation Guidelines Part 17 ilable. ilable. ilable. er = 1) able | | | |
| Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/wate | > 100 ^{°0} Classifi Not ava Not ava Not ava 1 (Wate emulsifi r): Not ava | ir = 1) C (> 212°F) ; Not classific cation Guidelines Part 17 ilable. ilable. ilable. er = 1) able ilable. | '3 Appendix H 7/10/20(|)2. | |
| Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/wate VOC content: | > 100 ° Classifi Not ava Not ava 1 (Wate emulsifi r): Not ava 0.1 %; 2 exempt | ir = 1) C (> 212°F) ; Not classific cation Guidelines Part 17 ilable. ilable. er = 1) able ilable. 27 g/l (by weight, calculat s calculated using SCAC | '3 Appendix H 7/10/200 |)2. | |
| Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/wate | > 100 ° Classifi Not ava Not ava 1 (Wate emulsifi r): Not ava 0.1 %; 2 exempt | ir = 1) C (> 212°F) ; Not classific cation Guidelines Part 17 ilable. ilable. er = 1) able ilable. 27 g/l (by weight, calculat s calculated using SCAC 00 mPa.s | '3 Appendix H 7/10/200 |)2. | |

10. STABILITY AND REACTIVITY

| Stability: | Stable under normal conditions of storage and use. |
|--------------------------------------|--|
| Hazardous reactions: | Will not occur. |
| Hazardous decomposition products: | None known |
| Incompatible materials: | Strong acids and oxidizing agents. |
| Reactivity: | Not available. |
| Conditions to avoid: | None known. |
| | 11. TOXICOLOGICAL INFORMATION |
| Relevant routes of exposure: | Eyes, Skin |

Potential Health Effects/Symptoms

| Inhalation: | Not a relevant route of exposure. |
|---------------|---|
| Skin contact: | Prolonged and/or repeated skin contact with this product may cause irritation. |
| Eye contact: | May cause irritation. |
| Ingestion: | Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|---|----------------------------------|--|
| Limestone | None | Nuisance dust |
| Silicon dioxide | Oral LD50 (RAT) = > 22,500 mg/kg | Nuisance dust |
| Distillates (petroleum), hydrotreated light | None | Irritant, Lung |
| Quartz (SiO2) | None | Immune system, Lung, Some evidence of carcinogenicity |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|----------------------------------|-----------------|---|
| Limestone | No | No | No |
| Silicon dioxide | No | No | No |
| Distillates (petroleum), hydrotreated light | No | No | No |
| Quartz (SiO2) | Known To Be Human Carcinogen. | Group 1 | No |

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

| Recommended method of disposal: | Dispose of according to Federal, State and local governmental regulations. |
|---------------------------------|--|
|---------------------------------|--|

Hazardous waste number:

It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

| U.S. Department of Transportation Ground (4 Proper shipping name: Hazard class or division: Identification number: Packing group: | 9 CFR) Not regulated None None None | |
|--|---|--|
| International Air Transportation (ICAO/IATA) Proper shipping name: Hazard class or division: Identification number: Packing group: | Not regulated None None None | |
| Water Transportation (IMO/IMDG)Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None | | |

15. REGULATORY INFORMATION

United States Regulatory Information

| CEPA DSL/NDSL Status: | All components are listed on or are exempt from listing on the Canadian Domestic Substances List. |
|--|---|
| Canada Regulatory Information | |
| California Proposition 65: | This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. |
| CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: | None above reporting de minimis None None above reporting de minimis |
| TSCA 12 (b) Export Notification: | None above reporting de minimis |
| TSCA 8 (b) Inventory Status: | All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. |

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 06/03/2015

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.